wallgrass™
covered by green

www.wallgrass.com

APPLICATION AREAS

Garden walls,
sports fields surroundings,
road sides and corners,
wall covering,
roofs and vertical
landscaping
areas.

SYSTEM DESCRIPTION

Wall grass has a perfect design and natural view and it helps you to cover anywhere fastly in a simple way.

FEATURES

Installation of Wallgrass is very easy. It is wire fence which is galvanized, PVC coated, specially formulated artificial grass which has resistance to UV.
It keeps its fresh look all seasons.

wallgrass

wallgrass™
covered by green

www.wallgrass.com

TECHNICAL INFORMATION			
Measurements	Height: 100 cm, 120 cm, 150 cm, 200 cm	Roll Length: 10 m	Roll Widht: 40 cm
Weight	2.500 r/m² (± %5)		
Galvanized wire	1,60x2 : 3,20 mm hot dipped galvanized double twisted		
Artificial grass	UV reinforced PVC grass		
Fireproofing	B2 type flame retardant additive		

INSTALLATION METHOD	
Roll Wallgrass	Wallgrass which is manufactured in rolls secured from the corners before assembly is done and after that fixed with special Wallgrass connection wires at intervals of 50 cm.
Panel Wallgrass	Wallgrass products which are produced as panels secured with special connection apparatus.

COLORS	
Wallgrass	Green, Red, Yellow, Metallic Gray
Connection Apparatus	Green, Red, Yellow, Mettalic Gray

ADVANTAGES	
View	Wallgrass has a natural look without any maintenance cost for years.
Maintenance free	Wallgrass does not need any maintenance to keep it clean.
Ecofriendly	It does not contain any harmful substances.You can use it at your garden or surroundings.

wallgrass™
covered by green

www.wallgrass.com

PRODUCT PACKAGING	
Wallgrass Roll	It is packed in 100 CM-200 CM Height and 40 cm widht in rolls and vertically packed in order not to give any damage to Wallgrass.
Wallgrass Panel	Can be loaded in different types without damaging Wallgrass panels.

PRODUCT STORAGE	
Wallgrass Roll	Between 0 ~ +30 ℃
Wallgrass Panel	Between 0 ~ +30 ℃

PRODUCTION AND INSTALLATION PERIODS			
Wallgrass Roll	Preperation of production: 3-5 Days	Production:1-7 Days	Installation:1-3 Days
Wallgrass Panel	Preperation of production: 3-5 Days	Production: 2-10 Days	Installation:1-5 Days

WARRANTY PERIODS		
UV	3 Years	10 % tolerance
Fireproof	3 Years	10 % tolerance
Thread Strength	3 Years	10 % tolerance

WALLGRASS

EXAMPLES OF APPLICATIONS

wallgrass™
covered by green

integral™ integrated systems
[İntegral Entegre Yapı Teknolojileri San. Tic. Ltd. Şti.]

+90 212 678 13 13 +90 212 678 13 33 info@wallgrass.com
Merkez/Head Office: Metro 34 Plaza No:23/70, İOSB Bedrettin Dalan Bulvarı **Başakşehir - İstanbul / TÜRKİYE**
Fabrika/Factory: Velimeşe OSB 93. Sokak No:101 **Çorlu - Tekirdağ / TÜRKİYE**